



SUPER SKIN

Nappa

nachik 

SUPER SKIN

Nappa

Thickness: 1.1 mm

Composition: PU 6.64%, PVC 74.37%, polyester 18.99%

Width@137cm (54")

Weight@1.12 kg/m²

Abrasion resistance: (BS EN ISO 12947-2/BS EN 14465: 2003 Annex a): >35,000 rubs

Change in shade @ 3000 revs: grade: grade 4

Colour fastness to rubbing (dry):BS EN ISO 105 x 12: 2002: 4-5

Colour fastness to rubbing (wet):BS EN ISO 105 x 12: 2002: 3-4

Colour fastness to light std 5:BS EN ISO 105 b02: 1999:5

Breaking Strength (ASTM D5034-09 2017): Warp 102, Fill 82

Yarn Slippage (ASTM D4034-91): Warp 236.5, Weft 62

Flame Retardant cigarette ignition resistance (NFPA 260 standard): PASS class 1

Care instructions:

Clean regularly with a damp cloth or sponge

(Use lukewarm water with a mild alkaline free soap –rinse with clean water)

Do not use: solvents / concentrated abrasive or solvent cleaning products / wax polish





301



302



319



321



322



324



323



309



308



320



317



318



316



315



311



310



303



307



313



314