

Composition: 70% PVC, 30% Polyester

Width: 138 cm

Weight: 850 gsm

Thickness: 1.3 mm

Abrasion resistance: (BS EN ISO 12947-2/BS EN 14465: 2003 Annex a) :
>100,000 rubs

Change in shade @ 3000 revs: grade:

grade 4-5 Abrasion (Wyzenbeek): (ASTM D4157-2007): 50,000 rubs, pass

Colour fastness to rubbing (dry): BS EN ISO 105 x 12: 2002:

4/5 Colour fastness to rubbing (wet): BS EN ISO 105 x 12: 2002: 4

Colour Fastness to Light: (BS EN ISO 105-B02:1999): Grade

Tear Strength: (BS EN ISO-3377-1:2002) : >20N

Flexing Resistance: (BS EN ISO 5402:2002): 50,000 cycles, Pass

Resistance to cold crack: (BS EN ISO 17233:2002): No cracking, Pass

Hydrolysis (Jungle testing): DIN EN ISO 32 100/ DIN 53 359: 7 weeks

Flame retardant: BF5852 SOURCE 0 & 1 (cigarette and matches): pass

Anti- bacterial finish

ROHS Standard

REACH Standard

Clean locally with damp cloth and mild detergent.

Usage: Upholstery; loose covers and cushions



BASKET 1



BASKET 2



BASKET 3



BASKET 4



BASKET 5



BASKET 6



BASKET 7



BASKET 8



BASKET 9



BASKET 10



BASKET 11



BASKET 12



BASKET 13



BASKET 14



BASKET 15



BASKET 16



BASKET 17



BASKET 18



BASKET 19



BASKET 20



BASKET 21



BASKET 22



BASKET 23



BASKET 24



BASKET 25



BASKET 26



BASKET 27



BASKET 28



BASKET 29



BASKET 30



BASKET 31



BASKET 32



BASKET 33



BASKET 34



BASKET 35